

ANT-GNSS-CSM-02-3m Series

GNSS antennas with SMA (male) connector



Features and Benefits

- Waterproof housing to protect against high-temperature and high-pressure water jets
- High-gain antenna to enhance performance
- Cone-shaped design to reduce the effects of snow and dust coverage
- 3-meter cable
- Flexible installation
- SMA connector (male) supported

Introduction

The ANT-GNSS-CSM-02-3m Series is an omnidirectional cone-shaped antenna suitable for GNSS applications. The antenna provides a gain of 2 dBic and is designed to operate in temperatures ranging from -40 to 85°C.

Specifications

Antenna Characteristics

Frequency	1561 to 1606 MHz
Antenna Type	Omni-directional
Typical Antenna Gain	Without low noise amplifier: -0.5 dBic @ 1561 MHz (BDS) 2 dBic @ 1575.42 MHz (GPS) 0.6 dBic @ 1598 to 1606 MHz (GLONASS) With low noise amplifier: 35 dB
Connector	SMA (male)
Impedance	50 ohms
Polarization	Vertical Linear
V.S.W.R.	< 2.0 (max.)


Physical Characteristics

Weight	Without cable and connector: 125 g (0.28 lb)
Dimensions	φ 60.5 (D) x 79.2 (H) mm
Radome Color	White
Radome Material	Plastic
Installation	Screw mount

Cable	RG-174
Cable Length	3 m
IP Rating	IP67
Environmental Limits	
Operating Temperature	-40 to 85°C (-40 to 185°F)
Storage Temperature (package included)	-40 to 85°C (-40 to 185°F)
Ambient Relative Humidity	5 to 95% (30°C, non-condensing)
Warranty	
Warranty Period	1 year
Details	See www.moxa.com/warranty

Dimensions

Unit: mm



Ordering Information

Model Name	Frequency	Antenna Type	Antenna Gain	Connector Type
ANT-GNSS-CSM-02-3m	1561 to 1606 MHz	Omnidirectional	2 dBic	SMA (male)

© Moxa Inc. All rights reserved. Updated May 23, 2023.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.